



Model USSA

Steel Wall Armor

UL Levels 1 – 8, NIJ I, II, IIIA, III

- ⇒ The USSA bullet resistant steel panel is a single sheet ballistic steel. USSA steel wall armor is an economical choice for wall construction and ideal for structural armor. This material conforms to UL and NIJ standards.
- ⇒ It is recommended for use in wall armor, judge's benches, counter protection and as finished opaque panels used in security storefronts.
- ⇒ Standard size: 48 x 96 sheets. Custom sizes available.
- ⇒ Standard finish: Prime paint finish.
- ⇒ Optional Finishes Include:
 Insulated, Clad in Stainless steel, Bronze, Anodized-Painted Aluminum

Product	Ballistic Protection	Nominal Thickness	Nominal Weight Sq. Ft.
USSA-0	NON	1/8"	5.125lbs.
USSA 1-3	Level 3	1/4"	10.25 lbs.
USSA 4-8	Level 4, 5, 7, 8 (UL) III (NIJ)	5/16"	13.5 lbs.

Installation: US Bullet Proofing recommends that pilot holes be drilled in the USSA panel to accommodate hanging metal on stud walls. The use of ----- screws at 12" – 24" OC is desirable. To insure complete protection at seams, we recommend incorporating 4" overlap strips of USSA or welded seams. Specialty equipment required for cutting, etc.

Disclaimer: In as much as U. S. Bullet Proofing has no control over the use to which others may put this

Revised 09